



FEATURES

- · Audible, visual strobe light and vibrating alarms
- Man down alarm leverages accelerometer technology
- · Rugged design with protective rubber enclosure
- Heavy duty metal clip
- Rechargeable Li-Ion battery - 12+ hours per charge
- Large LCD Display
 - CO2
 - Temperature
 - % Relative Humidity
- · Calibrate using nitrogen or ambient air
- No over-exposure or negative memory effects
- IP54 housing protects against dust and rain
- Programmable alarm settings

SPECIFICATIONS

- Measurement Range: 0-5% CO2
- Sensor Accuracy: ±200ppm ±10% reading value
- CO2 Measurement Interval: 2 seconds
- Audible Alarm: 90 dB @ 10 cm
- Temperature Accuracy: ±0.9°F (±0.5°C)
- Humidity Range: 0-90% noncondensing
- Humidity Accuracy: ±4.5% RH
- **Size:** 2.0 x 4.0 x 4.0 in. (50.8 x 101.6 x 101.6mm.)
- Weight: 4 oz.
- Sensor Life Expectancy: 15 years

INCLUDES

- 110/240 VAC USB Wall Adapter
- USB Cable for Charging
- User Manual

ADDITIONAL PERSONAL DEVICES

- SAN-20 Personal O2 Safety Monitor
- SAN-30 Personal CO Safety Monitor

INDUSTRIES



Brewing



Restaurants



Safety



Agriculture



Beverage