

## **Vacuum Packaging System Spec Sheet**

# GREENVAC

### ITEM: GV150-GN1/2



#### **DESCRIPTION**

The robust, stainless steel 150-1/2 GN vacuum packaging system is standard equipped with a vacuum lid, gasket seal & nozzle. NSF certified

#### WARRANTY

All models shown come with Invacus standard one year warranty against defects in materials and workmanship. For full warranty details, please refer to: Invacus.com





#### **FEATURES**

GN1/2 are manufactured with 17/18 gauge chrome nickel steel. In comparison, conventional containers are manufactured with 22/24 gauge steel. Oven safe.

#### LIDS

Developed from a high performance plastic (Tritan) Product Facts:

- •High impact resistance
- High weather resistance
- · High chemical resistance
- Perfect abrasions-resistance and sliding condition
- •Minimum water absorption very high dimensions stability
- •Minimum specific weight
- •Excellent high impact resistance
- •High barrier-character
- •Lids short term resistant to temperatures up to 194°F (dishwater)

#### **SEALS**

The gaskets are made of food compatible silicone.

The valve is produced from latex.

All GreenVAC components are new developments for a use in high vacuum. The atmospheric pressure in such a vacuum has a value of 900 - 1700kg / cm2 depending on the size of GreenVAC container!

Used in connection with:

- •Henkelman Vacuum Machine w/External Adapter.
- •A retrofitted chamber machine.
- •Directly in the chamber of a standard vacuum machine, sizes are dependent on the chamber size.

GREEN VAC




www.invacus.com

Invacus LLC Sales and Technical Support 493 W Fullerton Ave Elmhurst IL, 60126 Ph: +1 331 979 2013 E: info@henkelmanusa.com Fax: +1 630 359 3875

# **Vacuum Packaging System Specs**

### DIMENSIONS IN INCHES



MODEL	DIMENSIONS (INCHES)			WEIGHT (LBS)	CAPACITY (US FLUID OZ)
GV150-GN1/2	L	W	Н	4.76 lbs	189.3 fl oz
	12.8"	10.4"	5.9"		





Invacus LLC Sales and Technical Support 493 W Fullerton Ave Elmhurst IL, 60126 Ph: +1 331 979 2013 E: info@henkelmanusa.com Fax: +1 630 359 3875