



FEATURES

- Large digital LCD display clearly indicates the current CO2 level and temperature.
- Easy to read display with all functions set from 3 push buttons.
- Power, upper limit, lower limit and photo sensor verification LEDs.
- IP54 case resistant to dust and water splash.

SPECIFICATIONS

- Measurement Range: 0-10,000 ppm
- Sensing Method: NDIR
- Accuracy: ± 70ppm or ± 5% CO2
- Sensor Response Time: < 2 minutes
- Operating Temperature: 32°-122° F
- Calibration: With fresh air (400 ppm)
- Sensor Life Expectnacy: 15 years
- Max Coverage Area: 1,500 sq.ft. with proper air handling

ELECTRICAL

- Power Supply: 110VAC Grounded
 - US Plug Only
- Power Consumption: 2 Watts
- Piggyback Cable: Peak Current <5A
 @ 250 VAC, SPST
- One Relay Output:
 - Peak Current < 5A @ 250 VAC, SPST.
 - Normally Open

ADDITIONAL

- PRT-0346 CO2 Tank Regulator with Solenoid Valve
- RAD-0501A CO2 Controller for Mushroom Farms & Growers
- RAD-0501E Day Night CO2 Monitor
 & Controller for Greenhouses European Model

INDUSTRIES



The Day Night CO2 Monitor and Grow Controller is used for tomatoes, lettuce, flowers, cannabis, and angriculture applications.

TYPICAL INSTALLATION

